




CODE 3001



Manicotto
PE100 - S5 Gas - PN 16 20°C



PE100 - SDR11 - S5
ACQUA: PFA (PN)=16 bar 20°C
GAS: MOP=10 bar; In Italia MOP=5 bar (D.M. 24/11/84, D.M. 16/4/2008 e successive modifiche)
Per il tempo di saldatura da utilizzare con tubo SDR26 contattare direttamente Unidelta.

CODE	DIM dxd [mm]	L [mm]	Z [mm]	W-SDR	PACK					
					RIF. 5	RIF. 10	RIF. 11	RIF. 12	RIF. 13	Sfusi
3001021000001	20x20	71	50	≤ 11	-	-	60	-	-	-
3001026000001	25x25	75	55	≤ 11	-	-	45	-	-	-
3001033000001	32x32	76	62	≤ 11	-	-	30	-	-	-
3001041000001	40x40	80	71	≤ 17	-	-	20	-	-	-
3001051000001	50x50	88	82	≤ 17	-	-	16	-	-	-
3001064000001	63x63	96	96	≤ 17	-	-	12	-	-	-
3001076000001	75x75	110	109	≤ 17	-	-	-	-	12	-
3001091000001	90x90	125	126	≤ 17	-	32	-	-	-	-
3001111000001	110x110	145	148	≤ 17	-	18	-	-	-	-
3001125000001	125x125	155	166	≤ 17	12	-	-	-	-	-
3001140000001	140x140	194	183	≤ 17	10	-	-	-	-	-
3001160000001	160x160	171	202	≤ 17	8	-	-	-	-	-
3001181000001	180x180	192	231	≤ 26	-	4	-	-	-	-
3001201000001	200x200	208	255	≤ 26	-	4	-	-	-	-
3001226000001	225x225	225	285	≤ 26	-	-	-	2	-	-
3001250000001	250x250	218	312	≤ 17	-	-	-	-	-	1
3001280000001	280x280	240	340	≤ 17	-	-	-	-	-	1
3001315000001	315x315	265	387	≤ 17	-	-	-	-	-	1
3001355000001	355x355	300	410	≤ 17	-	-	-	-	-	1
3001400000001	400x400	355	485	≤ 17	-	-	-	-	-	1