


CODE 3002



Manicotto di riduzione
PE100 - S5 Gas - PN 16 20°C



PE100 - SDR11 - S5
ACQUA: PFA (PN)=16 bar 20°C
GAS: MOP=10 bar; In Italia MOP=5 bar (D.M. 24/11/84, D.M. 16/4/2008 e successive modifiche)
Per il tempo di saldatura da utilizzare con tubo SDR26 contattare direttamente Unidelta.

CODE	DIM dxd ₁ [mm]	L [mm]	Z [mm]	W-SDR	PACK				
					RIF. 10	RIF. 11	RIF. 12	RIF. 13	Sfusi
3002026021001	25x20	79	55	≤ 11	-	40	-	-	-
3002033021001	32x20	82	62	≤ 11	-	40	-	-	-
3002033026001	32x25	82	62	≤ 11	-	35	-	-	-
3002041033001	40x32	83	71	≤ 11	-	27	-	-	-
3002051033001	50x32	92	82	≤ 11	-	16	-	-	-
3002064033001	63x32	103	96	≤ 11	-	12	-	-	-
3002064041001	63x40	103	96	≤ 11	-	12	-	-	-
3002064051001	63x50	103	96	≤ 11	-	12	-	-	-
3002076064001	75x63	110	109	≤ 17	-	-	-	-	-
3002091064001	90x63	125	126	≤ 17	-	-	-	8	-
3002091076001	90x75	126	126	≤ 17	-	-	-	-	-
3002111064001	110x63	145	148	≤ 17	18	-	-	-	-
3002111091001	110x90	146	148	≤ 17	-	-	-	-	-
3002125063001	125x63	163	176	≤ 17	-	-	-	-	1
3002125090001	125x90	206	176	≤ 17	-	-	-	-	1
3002125110001	125x110	168	176	≤ 17	-	-	-	-	1
3002160110001	160x110	229	217	≤ 17	-	-	-	-	1
3002180125001	180x125	219	240	≤ 17	-	-	-	-	1
3002200160001	200x160	239	261	≤ 17	-	-	-	-	1
3002225160001	225x160	239	285	≤ 17	-	-	-	-	1
3002250180001	250x180	239	319	≤ 17	-	-	-	-	1
3002315250001	315x250	274	378	≤ 17	-	-	-	-	1