




CODE 3626

Giunto di transizione ottone PE filettato maschio
PE100/SDR 11 - S5 Gas - PN 16 20°C



PE100 - SDR11 - S5
ACQUA: PFA (PN)=16 bar 20°C
GAS: MOP=10 bar; In Italia MOP=5 bar (D.M. 24/11/84, D.M. 16/4/2008 e successive modifiche)

| CODE | DIM dxg [mmxin.] | L1 [mm] | L2 [mm] | PACK | |
|---------------|---------------------|------------|------------|--------|---------|
| | | | | RIF. 2 | RIF. 11 |
| 3626020002001 | 20x1/2" | 42 | 95 | - | 70 |
| 3626025003001 | 25x3/4" | 44 | 103 | - | 45 |
| 3626032004001 | 32x1" | 47 | 112 | - | 30 |
| 3626040005001 | 40x1"1/4 | 52 | 124 | - | 15 |
| 3626050006001 | 50x1"1/2 | 58 | 135 | - | 10 |
| 3626063007001 | 63x2" | 66 | 153 | - | 6 |
| 3626075008001 | 75x2"1/2 | 73 | 165 | 6 | - |
| 3626090009001 | 90x3" | 82 | 181 | 4 | - |
| 3626110010001 | 110x4" | 85 | 193 | 4 | - |