

CODE 2550



Tubo PE-X/Al/PE-X preaislado para uso sanitario y calefacción suministrado en rollos - Color azul
 Vorisoliertes PE-X/Al/PE-X Rohr für Sanitären- und Heizungsgebrauch in Rollen geliefert - Hellblau
 Euroclasse B_L-s1, d0



CODE	d _e [mm]	e [mm]	d _{e iso} [mm]	e _{iso} [mm]	d _i [mm]	e all [mm]	Pt [Kg/m]	Vf [l/m]	F [m]
2550001420050	14	2,0	26	6	10	0,20	0,118	0,079	R50
2550001620050	16	2,0	28	6	12	0,20	0,144	0,113	R50
2550001620100									R100
2550001820050	18	2,0	30	6	14	0,20	0,163	0,154	R50
2550022020050°	20	2,0	32	6°	16	0,25	0,186	0,201	R50
2550002020050	20	2,0	40	10	16	0,25	0,204	0,201	R50
2550002525025	25	2,5	45	10	20	0,30	0,295	0,314	R25
2550002630025	26	3,0	46	10	20	0,30	0,328	0,314	R25
2550002630050									R50
2550003230025	32	3,0	52	10	26	0,40	0,420	0,531	R25

° Espesor aislamiento NO conforme a la ley italiana 10/91

° Die Dicke der Isolierung entspricht NICHT das italienische Gesetz 10/91